



ENERG
енергия · ενεργεια



NIBE

ERS S40-350



41
dB



386 m³/h



ENERGIA · ЕНЕРГИЯ · ΕΝΕΡΓΕΙΑ · ENERGIJA · ENERGY · ENERGIE · ENERGI

2016

1254/2014

Technical Product Fiche

Suppliers name	NIBE
Model identification	ERS S40-350
Specific energy consumption SEC kWh/(m ² *a) for: cold, average, warm climates	SECcold: -75,3 ; SECAverage : -38,3 ; SECwarm: -14,4
RVU/NRVU/Unidirectional / Bidirectional	RVU - Bidirectional
Type of drive installed	EC motor with 0-100 % modulation range
Type of heat recovery (recuperative, regenerative, non)	Regenerative
Thermal efficiency of heat recovery %	83
Maximum airflow (m ³ /h)	386
Electric Power input of fan drive at maximum airflow - W	161
Sound Power level (Lwa) at reference airflow Lwa	41
Reference airflow rate (m ³ /s)	0,075
Reference pressure difference (min. 50Pa) – (Pa)	50
Specific power input at reference airflow – SEL/ SPI (W/ m ³ /h)	0,252
Control factor	0,85
Declared maximum internal and external leakage rates (%)	Internal: 2,8% ; External: 0,38%
Mixing rate of non ducted bidirectional ventilation units	Not applicable
Position and description of visual filter warning	After a specific time the display will tell that it is time to clean the filters or replace them with new ones.
Instructions for installing supply/exhaust grilles i facade for unidirectional devices	Not applicable
Internet adress for pre-/disassembly instructions	www.nibe.eu (manual)
Sensitivity for pressure variation for units without ducts + and - 20Pa	Not applicable
For non ducted units - the indoor/outdoor air tightness in (m ³ /h)	Not applicable
The annual electricity consumption AEC per 100 m ² (kWh electricity /a) for climates : Average, Warm, Cold	AECcold=810 ; AECAverage=273 ; AECwarm=228
The annual heating saved AHS in primary energy (kWh prim/a) per 100 m ² for climates : Average, Warm, Cold	AHScold=8686 ; AHSaverage=4440 AHSwarm=2008